


**Features:**

- 1350V Field Stop Trench Technology
- High Speed Switching
- Low Conduction Loss
- Positive Temperature Coefficient
- Easy Parallel Operation
- RoHS Compliant
- JEDEC Qualification



**Applications :**

Induction Heating, Soft Switching Application, UPS, Welder, Inverter

Device	Package	Marking	Remark
TGAN20N135FDL2	TO-3PN	TGAN20N135FDL2	RoHS

**Absolute Maximum Ratings**

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CES}$	1350	V
Gate-Emitter Voltage, Forward	$V_{GES}$	$\pm 25$	V
Continuous Collector Current  $T_C = 25^\circ\text{C}$	$I_c$	40	A
		20	A
Pulsed Collector Current (Note 1)	$I_{CM}$	100	A
Diode Continuous Forward Current	$I_F$	20	A
Power Dissipation  $T_C = 25^\circ\text{C}$	$P_D$	223	W
		86	W
Operating Junction Temperature	$T_{vj}$	-55 ~ 150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 ~ 150	$^\circ\text{C}$
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	$T_L$	300	$^\circ\text{C}$

Notes :

- (1) Repetitive rating : Pulse width limited by maximum junction temperature , During production, high current switching capability is 100% verified with the inductive load single-pulse switching test. ( $I_c=100\text{A}$ )

**Thermal Characteristics**

Parameter	Symbol	Value	Unit
Maximum Thermal resistance, Junction-to-Case	$R_{\theta JC}$ (IGBT)	0.56	$^\circ\text{C/W}$
Maximum Thermal resistance, Junction-to-Case	$R_{\theta JC}$ (DIODE)	3	$^\circ\text{C/W}$
Maximum Thermal resistance, Junction-to-Ambient	$R_{\theta JA}$	40	$^\circ\text{C/W}$

**Electrical Characteristics of the IGBT  $T_{vj}=25^\circ\text{C}$ , unless otherwise noted**

Parameter	Symbol	Test condition	Min.	Typ.	Max.	Units
<b>OFF</b>						
Collector – Emitter Breakdown Voltage	$\text{BV}_{\text{CES}}$	$V_{\text{GE}} = 0\text{V}, I_{\text{C}} = 1\text{mA}$	1350	--	--	V
Zero Gate Voltage Collector Current	$I_{\text{CES}}$	$V_{\text{CE}} = 1350\text{V}, V_{\text{GE}} = 0\text{V}$	--	--	1	mA
Forward Gate – Emitter Leakage Current	$I_{\text{GES(F)}}$	$V_{\text{CE}} = 0\text{V}, V_{\text{GE}} = \pm 25\text{V}$	--	--	$\pm 500$	nA
<b>ON</b>						
Gate – Emitter Threshold Voltage	$V_{\text{GE(TH)}}$	$V_{\text{GE}} = V_{\text{CE}}, I_{\text{C}} = 20\text{mA}$	4.0	6.0	8.0	V
Collector – Emitter Saturation Voltage	$V_{\text{CE(SAT)}}$	$V_{\text{GE}} = 15\text{V}, I_{\text{C}} = 20\text{A}, T_{vj} = 25^\circ\text{C}$	1.5	1.8	2.2	V
		$V_{\text{GE}} = 15\text{V}, I_{\text{C}} = 20\text{A}, T_{vj} = 125^\circ\text{C}$	--	2.2	--	V
<b>DYNAMIC</b>						
Input Capacitance	$C_{\text{IES}}$	$V_{\text{CE}} = 30\text{V}, V_{\text{GE}} = 0\text{V}$ $f = 1\text{MHz}$	--	1950	--	pF
Output Capacitance	$C_{\text{OES}}$		--	55	--	pF
Reverse Transfer Capacitance	$C_{\text{RES}}$		--	40	--	pF
<b>SWITCHING</b>						
Turn-On Delay Time	$t_{d(\text{on})}$	$V_{\text{CC}} = 600\text{V}, I_{\text{C}} = 20\text{A}$ $R_{\text{G}} = 10\Omega, V_{\text{GE}} = 15\text{V}$ Inductive Load, $T_{vj} = 25^\circ\text{C}$	--	25	--	ns
Rise Time	$t_r$		--	30	--	ns
Turn-Off Delay Time	$t_{d(\text{off})}$		--	175	--	ns
Fall Time	$t_f$		--	105	155	ns
Turn-On Switching Loss	$E_{\text{ON}}$		--	2.5	3.7	mJ
Turn-Off Switching Loss	$E_{\text{OFF}}$		--	0.76	1.15	mJ
Total Switching Loss	$E_{\text{TS}}$		--	3.26	4.85	mJ
Turn-On Delay Time	$t_{d(\text{on})}$		--	25	--	ns
Rise Time	$t_r$	$V_{\text{CC}} = 600\text{V}, I_{\text{C}} = 20\text{A}$ $R_{\text{G}} = 10\Omega, V_{\text{GE}} = 15\text{V}$ Inductive Load, $T_{vj} = 125^\circ\text{C}$	--	30	--	ns
Turn-Off Delay Time	$t_{d(\text{off})}$		--	190	--	ns
Fall Time	$t_f$		--	235	--	ns
Turn-On Switching Loss	$E_{\text{ON}}$		--	2.5	3.7	mJ
Turn-Off Switching Loss	$E_{\text{OFF}}$		--	1.52	2.28	mJ
Total Switching Loss	$E_{\text{TS}}$		--	4.02	5.98	mJ
Total Gate Charge	$Q_g$	$V_{\text{CC}} = 600\text{V}, I_{\text{C}} = 20\text{A}$ $V_{\text{GE}} = 15\text{V}$	--	120	180	nC
Gate-Emitter Charge	$Q_{\text{ge}}$		--	15	20	nC
Gate-Collector Charge	$Q_{\text{gc}}$		--	60	90	nC

**Electrical Characteristics of the DIODE  $T_{vj}=25^{\circ}\text{C}$ , unless otherwise noted**

Parameter	Symbol	Test condition		Min.	Typ.	Max.	Units	
Diode Forward Voltage	$V_{FM}$	$I_F = 20\text{A}$	$T_{vj} = 25^{\circ}\text{C}$	--	2.4	2.8	V	
			$T_{vj} = 125^{\circ}\text{C}$	--	2.75	--		
Reverse Recovery Time	$t_{rr}$	$I_F = 20\text{A},$ $di/dt = 200\text{A}/\mu\text{s}$	$T_{vj} = 25^{\circ}\text{C}$	--	265	425	ns	
			$T_{vj} = 125^{\circ}\text{C}$	--	295	--		
Reverse Recovery Current	$I_{rr}$		$T_{vj} = 25^{\circ}\text{C}$	--	23	35	A	
			$T_{vj} = 125^{\circ}\text{C}$	--	28.5	--		
Reverse Recovery Charge	$Q_{rr}$		$T_{vj} = 25^{\circ}\text{C}$	--	3030	6000	nC	
			$T_{vj} = 125^{\circ}\text{C}$	--	4170	--		

## IGBT Characteristics

Fig. 1 IGBT Output Characteristics




Fig. 3 IGBT Saturation Voltage  
vs. Junction Temperature




Fig. 5 IGBT Saturation Voltage vs. Gate Bias




Fig. 2 IGBT Saturation Voltage Characteristics




Fig. 4 IGBT Saturation Voltage vs. Gate Bias





Fig. 6 Capacitance Characteristics



## IGBT Characteristics

Fig. 7 Turn-on Time vs. Gate Resistor




Fig. 9 Switching Loss vs. Gate Resistor




Fig. 11 Turn-off Time vs. Collector Current




Fig. 8 Turn-off Time vs. Gate Resistor




Fig. 10 Turn-on Time vs. Collector Current





Fig. 12 Switching Loss vs. Collector Current



## IGBT Characteristics

Fig. 13 Gate Charge Characteristics




Fig. 15 RBSOA




Fig. 17 Load Current vs. Frequency




Fig. 14 SOA




Fig. 16 Transient Thermal Impedance of IGBT





Fig. 18 Load Current vs. Frequency



## Diode Characteristics

Fig. 19 Diode Conduction Characteristics




Fig. 20 Reverse Recovery Current vs. Forward Current




Fig. 21 Reverse Recovery Charge vs. Forward Current






Fig. 22 Reverse Recovery Time vs. Forward Current



## TO-3PN MECHANICAL DATA



SYMBOL	mm		
	MIN	NOM	MAX
A	4.60	4.80	5.00
b	0.80	1.00	1.20
b1	1.80	2.00	2.20
b2	2.80	3.00	3.20
c	0.55	0.60	0.75
c1	1.45	1.50	1.65
D	15.40	15.60	15.80
E	19.20	19.65	20.10
e	5.15	5.45	5.75
L1	3.30	3.50	3.70
L2	19.80	20.00	20.20
ΦP1	3.30	3.40	3.50
ΦP2	(3.20)		
Q	2.20	2.40	2.60
q1	4.80	5.00	5.20

### Disclaimer

TRinno technology reserves the right to make changes without notice to products herein to improve reliability, performance, or design. The information given in this document is believed to be accurate and reliable. However, it shall in no event be regarded as a guarantee of conditions and characteristics. With respect to any information regarding the application of the device, TRinno technology hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of patent rights of any third party.